



DEV9108-53

# CG53-10 Replacement Cartridge

## Drop-in Replacement Cartridge for Foodservice Applications



CG53-10 Replacement Cartridge: DEV9108-53

### BENEFITS

Submicron carbon block reduces extra fine particles and dirt from drinking water

Effectively reduces contaminants such as Cryptosporidium and Giardia cysts

Effectively reduces unwanted tastes, odor and chlorine

High porosity design prevents the cartridge from plugging before its adsorption capacity is exhausted

Improves the taste of beverages such as fountain drinks and coffee

Helps keep equipment running at peak efficiency and keeps maintenance costs down

Drop-in design fits most 10" bowls

### INSTALLATION TIPS

- Install vertically so bowls hang down.
- Allow 2-1/2" clearance below the cartridge for easy cartridge replacement
- Make sure O-ring on bowl is sufficiently lubricated
- Always screw on bowls by hand; do not use a housing wrench

### OPERATION TIPS

- Change cartridges on a regular 6 month preventative maintenance program
- Change cartridges when capacity is reached or when pressure decreases
- Always inspect O-ring; change and/or lubricate if necessary
- Always flush the filter cartridge at time of installation and cartridge change

### APPLICATION/SIZING

For foodservice applications  
Drop-in cartridge for taste, odor, sediment and cyst reduction  
Capacity: 10,000 gallons (37,800L)

## S P E C I F I C A T I O N S

Overall Dimensions:  
9.75" H x 2.87" Diameter


Service Flow Rate:  
Maximum 2.0 gpm (7.6 Lpm)

Pressure Requirements:  
30 - 125 psi (2.1 – 8.6 bar), non-shock

Temperature: 40 - 100°F (4.4 - 38°C)

No electrical connection required

# CG53-10 Replacement Cartridge



The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

## W A R R A N T Y

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.

**EVERPURE**®

Worldwide Headquarters:  
EVERPURE, LLC  
1040 Muirfield Drive  
Hanover Park, Illinois 60133  
Toll Free (800) 323-7873  
Tel (630) 307-3000  
Fax (630) 307-3030  
<http://www.everpure.com>

In Europe:  
Pentair Water Belgium B.V./B.A.  
Industriepark Wolfstree  
Toekomstlaan 30  
B-2200 Herentals  
BELGIUM  
TEL: +32.(0).14.283.500  
FAX: +32.(0).14.283.505

In Japan:  
Hashimoto MN Bldg. 7F  
3-25-1 Hashimoto Sagamihara-Shi  
Kanagawa 229-1103  
JAPAN  
TEL: 81.(0)42.775.3011  
FAX: 81.(0)42.775.3015